

## Technical Data Sheet

Last revised: 01-2019

---

### MORDRY® Calcium 4 WD

**MORDRY® Calcium 4 WD** is a water-dispersible Calcium salt of saturated branched mixture of acids.

---

#### **Specifications:**

Specific gravity @ 25°C	:	0.85 – 1.00 g/cm <sup>3</sup>
Color Gardner	:	max. 6
Metal content	:	ca. 4.0%

Methods of analysis can be received upon request

---

#### **Applications and usage:**

**MORDRY® Calcium 4 WD** is a drier for coating systems. Calcium functions to improve the drying characteristics at low temperatures and improves the resistance to wrinkling as a result of high levels of cobalt. It is considered as auxiliary drier used most often in combination with lead, zirconium and/or cobalt driers.

The normal use level range for **MORDRY® Calcium 4 WD** is between **2.75%** and **8.1%** calculated on resin solids.

This dose can be considered as a guideline. The optimum combination and concentrations will depend on the total formulation characteristics.

---

#### **Safety and Handling:**

**MORDRY® Calcium 4 WD** should be handled in accordance with good industrial practice. Detailed information can be found in the Safety Data Sheet.

---

#### **Storage:**

**MORDRY® Calcium 4 WD** should be stored at temperatures between 5 °C and 32 °C. Although **MORDRY® Calcium 4 WD** will not freeze under ordinary conditions, best results can be insured if it is kept between the recommended temperatures prior to use. When kept in an original unopened container, it will keep up to 2 years from the date of manufacture. The production date is indicated on the container.

---

#### **Packaging:**

170 kg non-returnable metallic container.

---