

Technical Data Sheet

Last revised: **01-2019**

MORDRY® Potassium 10

MORDRY® Potassium 10 is a drier for coatings based on Potassium salt of saturated branched C8 acids in mineral spirit.

Specifications:

Specific gravity @ 25°C	:	0.95 – 1.03 g/cm ³
Color (Gardner)	:	max. 3
Metal content	:	ca. 10.0%

Methods of analysis can be received upon request

Applications and usage:

MORDRY® Potassium 10 is a promoter for driers in coating systems. It works synergistically with cobalt in unsaturated polyester thermosetting systems.

The normal use of level range for **MORDRY® Potassium 10** is:

0.5-2.0% calculated on resin solids

This dosage can be considered as a guideline. The optimum combination and concentrations will depend on the total formulation characteristics.

Safety and Handling:

MORDRY® Potassium 10 should be handled in accordance with good industrial practice. Detailed information can be found in the Safety Data Sheet.

Storage:

MORDRY® Potassium 10 should be stored at temperatures between 5 °C and 32 °C. Although **MORDRY® Potassium 10** will not freeze under ordinary conditions, best results can be insured if it is kept between the recommended temperatures prior to use. When kept in an original unopened container, it will keep up to 2 years from the date of manufacture. The production date is indicated on the container.

Packaging:

200 kg non-returnable metallic container.
